




TECHNICAL DATA BOOK

CB HORIZONTAL SPLIT CASING PUMP

50HZ



SPECIFICATION

Main Applications and Product Features	A-1
Model Code	A-2
Specification	A-3

TECHNICAL DATA

Impeller Diameter	B-1
Noise Data	B-2
Nominal Dimension of Parts	B-3

DIMENSIONS

Dimensions of Bare Shaft Pump	C-1, 2, 3, 4
Dimensions of Pump with motor	C-5, 6, 7, 8, 9, 10, 11

CONSTRUCTION

Sectional View of Pump	D-1
Selection View of Mechanical Seal	D-2

SELECTION CHART

50Hz m ³ /min · m – 2P, 4P, 6P	E-1, 2, 3
---	-----------

PERFORMANCE CURVES**50Hz – 2P**

125X80 CBJ , 150X100 CBJ , 150X125 CBH , 150X125 CBJ , 200X125 CBH

50Hz – 4P

125X80 CBJ , 125X80 CBK , 125X100 CBK , 150X100 CBJ , 150X100 CBK ,
 150X125 CBH , 150X125 CBJ , 150X150 CBG , 200X100 CBK , 200X125 CBH ,
 200X125 CBJ , 200X150 CBG , 200X150 CBH , 200X150 CBJ , 200X200 CBF ,
 250X150 CBH , 250X150 CBJ , 250X150 CBK , 250X200 CBF , 250X200 CBGX ,
 250X200 CBGY , 250X200 CBH , 300X150 CBK , 300X200 CBG , 300X200 CBH ,
 300X200 CBJX , 300X200 CBJY , 300X250 CBFX , 300X250 CBFY , 300X250 CBG ,
 300X250 CBH , 350X250 CBG , 350X250 CBH , 350X250 CBJ , 350X300 CBF ,
 400X300 CBG , 400X300 CBH , 400X300 CBJX , 400X350 CBF , 400X400 CBF

50Hz – 6P

350X250 CBH , 350X250 CBJ , 400X300 CBG , 400X300 CBH , 400X300 CBJX ,
 400X300 CBJY , 400X400 CBF , 450X300 CBH , 450X350 CBG , 450X350 CBJ ,
 450X400 CBF , 500X350 CBG , 500X350 CBH

Main Applications

Water Supply

- Water supply duties for municipalities
- Irrigation (flooding, sprinkler, farming)
- Drainage clean water

General Industrial Systems

- Water supply
- Process cooling and chilled water systems
- Cooling systems and water condensing systems
- Water circulation
- Boiler feed systems

Building

- General water supply
- Air conditioning
- Water condensing systems
- Fire protection



Product Features

Energy-saving Design

- World top class pump efficiency achieved.
- Major improvement over our previous models by impeller designed using our proprietary 3D inverse design technology.
- Higher efficiency means lower energy consumption and motor output, and more compact size.

Simple Maintenance

- Very compact design for ease of installation and permits minimum maintenance.
- Axially split casing allows the easy removal of the top casing for inspection and service.
- Shield bearings eliminate need for adding or exchanging lubricating oil.
- Shaft seal flushing and quenching piping not required for the standard application.



SPECIFICATION - General Description

A-3

Pump specification

Capacities		To 53 m ³ /min (50Hz)
Heads		To 135 m (50Hz)
Liquid Handled	Type of liquid	Clean water, Industrial water, River water
	Temperature	0 to 80°C
Max. Operating Pressure		16bar (1.6MPa)
Construction	Impeller	Closed double suction
	Shaft seal	Mechanical Seal
	Flushing	No Flushing
	Ball Bearing	Sealed ball bearing (grease lubrication)
Flange		JIS 16K RF, GB PN16 RF
Material	Casing	FC250 or FCD450 *1
	Impeller	CAC406 or SCS13 *2
	Main shaft	SUS420J1
	Mechanical Seal	Ceramic/Carbon NBR or Silicon carbide/Carbon FPM *3

*1: It is applicable for Model 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH

*2: It is applicable for Model 400X300CBJX, 400X300CBJY, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH

*3: It is applicable for Model 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 450X350CBJ, 500X350CBH

Motor specification

Number of poles	2 poles	4 poles	6 poles
Synchronous speed	3000min ⁻¹	1500min ⁻¹	1000min ⁻¹
Phase	3 Phase		
Voltage	380V ±10%		
Type	Totally enclosed fan cooled (indoors)		
Protection	IP55		
Frequency	30~50Hz		

* Optional:

1. Totally enclosed fan cooled (indoors)
2. Varying frequency running (5~50Hz)
3. Other types of motor that user require

Accessories**Standard:**

- Common base
- Coupling
- Coupling guard

Optional:

- Disc coupling

TECHNICAL DATA - Impeller Data

B-1

— Not applicable Model

Unit : mm

Model	50Hz					
	2P		4P		6P	
	Max	Min	Max	Min	Max	Min
125X80CBJ	228	191	228	191	—	—
125X80CBK	—	—	292	234	—	—
125X100CBK	—	—	328	262	—	—
150X100CBJ	255	214	255	214	—	—
150X100CBK	—	—	368	294	—	—
150X125CBH	216	166	216	166	—	—
150X125CBJ	286	239	286	239	—	—
150X150CBG	—	—	196	165	—	—
200X100CBK	—	—	413	330	—	—
200X125CBH	242	186	242	186	—	—
200X125CBJ	—	—	319	267	—	—
200X150CBG	—	—	220	185	—	—
200X150CBH	—	—	272	209	—	—
200X150CBJ	—	—	357	299	—	—
200X200CBF	—	—	197	165	—	—
250X150CBH	—	—	306	235	—	—
250X150CBJ	—	—	401	336	—	—
250X150CBK	—	—	463	370	—	—
250X200CBF	—	—	221	185	—	—
250X200CBGX	—	—	247	207	—	—
250X200CBGY	—	—	277	233	—	—
250X200CBH	—	—	343	264	—	—
300X150CBK	—	—	521	416	—	—
300X200CBG	—	—	311	261	—	—
300X200CBH	—	—	386	296	—	—
300X200CBJX	—	—	448	376	—	—
300X200CBJY	—	—	503	421	—	—
300X250CBFX	—	—	247	208	—	—
300X250CBFY	—	—	277	232	—	—
300X250CBG	—	—	349	293	—	—
300X250CBH	—	—	432	332	—	—
350X250CBG	—	—	392	329	—	—
350X250CBH	—	—	486	373	486	373
350X250CBJ	—	—	563	472	563	472
350X300CBF	—	—	311	261	—	—
400X300CBG	—	—	440	369	440	369
400X300CBH	—	—	544	418	544	418
400X300CBJX	—	—	631	528	631	528
400X300CBJY	—	—	—	—	707	593
400X350CBF	—	—	349	293	—	—
400X400CBF	—	—	391	328	391	328
450X300CBH	—	—	—	—	612	470
450X350CBG	—	—	—	—	494	414
450X350CBJ	—	—	—	—	793	665
450X400CBF	—	—	—	—	439	370
500X350CBG	—	—	—	—	555	465
500X350CBH	—	—	—	—	687	528

TECHNICAL DATA - Noise Data

B-2

— Not applicable Model			Unit : bB(A)
Model	50Hz		
	2P	4P	6P
125X80CBJ	77	72	—
125X80CBK	—	74	—
125X100CBK	—	76	—
150X100CBJ	79	73	—
150X100CBK	—	78	—
150X125CBH	77	72	—
150X125CBJ	80	75	—
150X150CBG	—	72	—
200X100CBK	—	79	—
200X125CBH	79	74	—
200X125CBJ	—	76	—
200X150CBG	—	72	—
200X150CBH	—	75	—
200X150CBJ	—	78	—
200X200CBF	—	73	—
250X150CBH	—	77	—
250X150CBJ	—	79	—
250X150CBK	—	80	—
250X200CBF	—	75	—
250X200CBGX	—	75	—
250X200CBGY	—	76	—
250X200CBH	—	78	—
300X150CBK	—	82	—
300X200CBG	—	78	—
300X200CBH	—	79	—
300X200CBJX	—	80	—
300X200CBJY	—	82	—
300X250CBFX	—	76	—
300X250CBFY	—	77	—
300X250CBG	—	79	—
300X250CBH	—	81	—
350X250CBG	—	81	—
350X250CBH	—	82	79
350X250CBJ	—	83	80
350X300CBF	—	78	—
400X300CBG	—	82	79
400X300CBH	—	84	80
400X300CBJX	—	84	81
400X300CBJY	—	—	83
400X350CBF	—	80	—
400X400CBF	—	81	78
450X300CBH	—	—	82
450X350CBG	—	—	80
450X350CBJ	—	—	84
450X400CBF	—	—	79
500X350CBG	—	—	82
500X350CBH	—	—	83

Note : The overall sound pressure level is the value measured 1m away from the pump unit and does not include driver noise.

This data is for reference and may differ from the actual noise level.

TECHNICAL DATA - Nominal Dimension of Parts


B-3

Model	Shaft Diameter (mm)	At Radial Bearing	At Thrust Bearing	CP side Mechanical Seal	CCP side Mechanical Seal
125X80CBJ	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
125X80CBK	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
125X100CBK	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X100CBJ	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X100CBK	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
150X125CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X125CBJ	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
150X150CBG	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X100CBK	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
200X125CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
200X125CBJ	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
200X150CBG	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X150CBH	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X150CBJ	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
200X200CBF	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
250X150CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X150CBJ	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
250X150CBK	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
250X200CBF	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X200CBGX	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X200CBGY	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
250X200CBH	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X150CBK	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X200CBG	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X200CBH	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
300X200CBJX	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X200CBJY	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
300X250CBFX	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
300X250CBFY	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X250CBG	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X250CBH	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
350X250CBG	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
350X250CBH	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
350X250CBJ	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
350X300CBF	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
400X300CBG	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100
400X300CBH	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
400X300CBJX	105	UCFS322C	UCFS320FD	1174 / T 8-1	1079 / T 8-1
400X300CBJY	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
400X350CBF	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
400X400CBF	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
450X300CBH	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100
450X350CBG	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
450X350CBJ	115	UCFS324C	UCFS322FD	1270 / T 8-1	1174 / T 8-1
450X400CBF	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
500X350CBG	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100
500X350CBH	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100

DIMENSIONS - Dimensions of Bare Shaft Pump

C-1

PUMP



■ Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	24	2	8	φ23
100	160	185	225	26	2	8	φ23
125	195	225	270	26	2	8	φ25
150	230	260	305	28	2	12	φ25
* 200	275	305	350	30	2	12	φ25
* 250	345	380	430	34	2	12	φ27
* 300	395	430	480	36	3	16	φ27
* 350	440	480	540	38	3	16	φ33
* 400	495	540	605	42	3	16	φ33
* 450	560	605	675	46	3	20	φ33
* 500	615	660	730	50	3	20	φ33

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH use the legal dimensions of Ductile Cast Iron

■ Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	22	3	8	φ19
100	156	180	220	24	3	8	φ19
125	184	210	250	26	3	8	φ19
150	211	240	285	26	3	8	φ23
* 200	266	295	340	30	3	12	φ23
* 250	319	355	405	32	3	12	φ28
* 300	370	410	460	32	4	12	φ28
* 350	429	470	520	36	4	16	φ28
* 400	480	525	580	38	4	16	φ31
* 450	548	585	640	40	4	20	φ31
* 500	609	650	715	42	4	20	φ34

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH use the legal dimensions of Ductile Cast Iron

*■ Ductile Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	275	305	350	26	2	12	φ25
250	345	380	430	28	2	12	φ27
300	395	430	480	30	3	16	φ27
350	440	480	540	34	3	16	φ33
400	495	540	605	38	3	16	φ33
450	560	605	675	40	3	20	φ33
500	615	660	730	42	3	20	φ33

*■ Ductile Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	266	295	340	20	3	12	φ23
250	319	355	405	22	3	12	φ28
300	370	410	460	24.5	4	12	φ28
350	429	470	520	26.5	4	16	φ28
400	480	525	580	28	4	16	φ31
450	548	585	640	30	4	20	φ31
500	609	650	715	31.5	4	20	φ34

DIMENSIONS - Dimensions of Bare Shaft Pump

C-2

■ 2P

Units:mm

MODEL	Size		Pump																Shaft						Wt (KG)
	Ds	Dd	A	B	C	E	F	G	H	I	J	K	M	N	O	P	Q	Z	L	R	T	U	V	W	
125X80CBJ	125	80	188	272	310	300	250	170	165	165	60	70	300	290	250	230	20	19	56	60.1	28	8	5	10	110
150X100CBJ	150	100	202.5	327.5	340	310	280	200	175	185	60	70	300	290	250	230	20	19	80	88	38	8	5	10	170
150X125CBH	150	125	210	335	360	330	290	180	185	175	80	90	380	360	310	270	25	19	80	84.5	38	8	5	10	170
150X125CBJ	150	125	234	366	370	340	315	224	205	205	80	90	380	360	310	270	25	19	90	102	48	9	5.5	14	200
200X125CBH	200	125	221.5	348.5	385	340	265	215	200	200	80	90	380	360	310	270	25	19	80	88	38	8	5	10	190

DIMENSIONS - Dimensions of Bare Shaft Pump

C-3

■ 4P

Units:mm

MODEL	Size		Pump																Shaft						Wt (KG)
	Ds	Dd	A	B	C	E	F	G	H	I	J	K	M	N	O	P	Q	Z	L	R	T	U	V	W	
125X80CBJ	125	80	188	272	310	300	250	170	165	165	60	70	300	290	250	230	20	19	56	60.1	28	8	5	10	110
125X80CBK	125	80	225	310	290	330	250	195	140	180	70	80	340	320	280	250	20	19	63	70	28	8	5	10	170
125X100CBK	125	100	245	370	345	370	280	230	180	200	80	90	380	360	310	270	25	19	80	91	38	8	5	10	240
150X100CBJ	150	100	202.5	327.5	340	310	280	200	175	185	60	70	300	290	250	230	20	19	80	88	38	8	5	10	170
150X100CBK	150	100	272	403	380	415	305	255	180	230	90	100	430	400	350	300	25	19	90	99	48	9	5.5	14	310
150X125CBH	150	125	210	335	360	330	290	180	185	175	80	90	380	360	310	270	25	19	80	84.5	38	8	5	10	170
150X125CBJ	150	125	234	366	370	340	315	224	205	205	80	90	380	360	310	270	25	19	90	102	48	9	5.5	14	200
150X150CBG	150	150	225	320	350	305	275	170	175	165	80	90	380	360	310	270	25	19	63	85	28	8	5	10	150
200X100CBK	200	100	285	420.5	430	465	350	275	185	255	100	110	480	450	390	340	25	24	100	109	48	9	5.5	14	430
200X125CBH	200	125	221.5	348.5	385	340	265	215	200	200	80	90	380	360	310	270	25	19	80	88	38	8	5	10	190
200X125CBJ	200	125	221.5	348.5	405	400	280	240	210	230	80	90	380	360	310	270	25	19	80	88	38	8	5	10	240
200X150CBG	200	150	255	350	370	330	285	205	185	185	80	100	430	400	350	300	25	19	80	91	28	8	5	10	210
200X150CBH	200	150	242.5	352.5	395	380	260	240	210	220	90	100	430	400	350	300	25	19	80	90	28	8	5	10	260
200X150CBJ	200	150	265.5	389.5	425	405	390	275	230	260	90	100	430	400	350	300	25	19	90	96	48	9	5.5	14	380
200X200CBF	200	200	245	340	385	380	320	210	200	200	90	100	430	400	350	300	25	19	63	70	28	8	5	10	230
250X150CBH	250	150	272	408	460	425	290	264	230	250	100	110	480	450	390	340	25	24	90	101	38	8	5	10	340
250X150CBJ	250	150	294	451	480	450	440	310	250	290	100	110	480	450	390	340	25	24	100	111	55	10	6	16	470
250X150CBK	250	150	345	520	480	520	390	310	205	285	110	120	550	520	450	400	30	24	110	123	65	11	7	18	630
250X200CBF	250	200	275	390	450	395	315	243	225	225	100	110	480	450	390	340	25	24	80	86	38	8	5	10	320
250X200CBGX	250	200	270	385	435	370	300	225	210	210	90	110	480	450	390	340	25	24	80	86	38	8	5	10	270
250X200CBGY	250	200	290	415	475	415	340	250	235	235	100	120	550	520	450	400	30	24	90	99	48	9	5.5	14	340
250X200CBH	250	200	284.5	420.5	505	475	350	280	260	280	110	120	550	520	450	400	30	24	100	109	48	9	5.5	14	470
300X150CBK	300	150	350	535	485	600	440	345	235	320	110	120	550	520	450	400	25	24	125	133	65	11	7	18	860
300X200CBG	300	200	310	460	525	465	355	270	260	265	110	120	550	520	450	400	30	24	100	115	48	9	5.5	14	580
300X200CBH	300	200	310	490	560	535	405	320	295	315	110	120	550	520	450	400	30	24	110	124	55	10	6	16	690
300X200CBJX	300	200	321	480	545	505	495	336	280	320	110	130	550	520	450	400	30	24	110	124.5	65	11	7	18	720
300X200CBJY	300	200	349	526	565	565	550	374	315	360	120	120	550	520	450	400	30	24	125	132.5	75	12	7.5	20	870
300X250CBFX	300	250	280	415	505	445	350	265	255	255	100	120	550	520	450	400	30	24	90	101	38	8	5	10	480
300X250CBFY	300	250	335	460	520	495	355	300	275	285	110	120	550	520	450	400	30	26	90	105	48	9	5.5	14	590
300X250CBG	300	250	370	525	600	560	450	305	307	300	135	150	620	700	500	550	38	26	110	121	65	11	7	18	780
300X250CBH	300	250	350	535	625	600	450	355	340	355	135	150	620	700	500	550	38	26	125	133	65	11	7	18	860
350X250CBG	350	250	390	570	585	585	440	340	270	335	135	150	620	700	500	550	38	26	125	132	75	12	7.5	20	890
350X250CBH	350	250	365	555	665	675	500	395	270	395	120	140	800	800	720	660	30	28	125	137	75	12	7.5	20	1180
350X250CBJ	350	250	394.5	620.5	645	635	615	420	335	405	120	140	700	700	620	560	30	28	140	160	95	14	9	25	1240
350X300CBF	350	300	360	510	600	560	450	330	275	320	130	150	620	700	500	550	38	26	100	107	55	10	6	16	830
400X300CBG	400	300	440	630	625	660	510	380	310	375	110	140	800	700	720	560	38	28	125	158	85	14	9	22	1400
400X300CBH	400	300	450	685	715	755	515	445	320	445	110	140	800	800	720	660	30	28	160	179	95	14	9	25	1670
400X300CBJX	400	300	559	756	725	710	690	470	380	455	140	140	800	800	660	660	30	28	160	170	105	16	10	28	1940
400X350CBF	400	350	420	575	645	625	510	370	321	360	150	135	700	700	550	550	38	26	110	124.5	65	11	7	18	1050
400X400CBF	400	400	470	645	725	690	505	410	380	405	130	160	860	800	780	640	35	30	125	132	75	12	7.5	20	1550

DIMENSIONS - Dimensions of Bare Shaft Pump

C-4


■ 6P

Units:mm

MODEL	Size		Pump																Shaft						Wt (KG)
	Ds	Dd	A	B	C	E	F	G	H	I	J	K	M	N	O	P	Q	Z	L	R	T	U	V	W	
350X250CBH	350	250	365	555	665	675	500	395	270	395	120	140	800	800	720	660	30	28	125	137	75	12	7.5	20	1180
350X250CBJ	350	250	394.5	620.5	645	635	615	420	335	405	120	140	700	700	620	560	30	28	140	160	95	14	9	25	1240
400X300CBG	400	300	440	630	625	660	510	380	310	375	110	140	800	700	720	560	38	28	125	158	85	14	9	22	1400
400X300CBH	400	300	450	685	715	755	515	445	320	445	110	140	800	800	720	660	30	28	160	179	95	14	9	25	1670
400X300CBJX	400	300	559	756	725	710	690	470	380	455	140	140	800	800	660	660	30	28	160	170	105	16	10	28	1940
400X300CBJY	400	300	432	658	815	800	630	515	420	510	130	160	860	900	780	740	35	30	140	145	95	14	9	25	1260
400X400CBF	400	400	470	645	725	690	505	410	380	405	130	160	860	800	780	640	35	30	125	132	75	12	7.5	20	1550
450X300CBH	450	300	475.5	679.5	800	800	580	490	380	500	130	160	860	860	780	740	35	30	140	144.5	85	14	9	22	1400
450X350CBG	450	350	414	606	705	740	555	420	360	420	120	160	860	800	780	640	35	30	125	148	75	12	7.5	20	1110
450X350CBJ	450	350	549	801	865	895	710	575	410	575	130	160	920	1000	840	840	35	30	160	180	115	18	11	32	1750
450X400CBF	450	400	454	620	780	750	565	450	415	445	130	160	920	900	840	740	30	30	125	134	65	11	7	18	1340
500X350CBG	500	350	475.5	679.5	775	830	600	465	395	470	120	160	920	900	840	740	35	30	140	162	85	14	9	22	1460
500X350CBH	500	350	533	767	855	950	650	550	425	560	140	160	920	1000	840	840	35	30	160	170	95	14	9	25	1880

DIMENSIONS - Dimension of Pump with Motor

C-5



■ Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	24	2	8	φ23
100	160	185	225	26	2	8	φ23
125	195	225	270	26	2	8	φ25
150	230	260	305	28	2	12	φ25
* 200	275	305	350	30	2	12	φ25
* 250	345	380	430	34	2	12	φ27
* 300	395	430	480	36	3	16	φ27
* 350	440	480	540	38	3	16	φ33
* 400	495	540	605	42	3	16	φ33
* 450	560	605	675	46	3	20	φ33
* 500	615	660	730	50	3	20	φ33

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH use the legal dimensions of Ductile Cast Iron

■ Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	22	3	8	φ19
100	156	180	220	24	3	8	φ19
125	184	210	250	26	3	8	φ19
150	211	240	285	26	3	8	φ23
* 200	266	295	340	30	3	12	φ23
* 250	319	355	405	32	3	12	φ28
* 300	370	410	460	32	4	12	φ28
* 350	429	470	520	36	4	16	φ28
* 400	480	525	580	38	4	16	φ31
* 450	548	585	640	40	4	20	φ31
* 500	609	650	715	42	4	20	φ34

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH use the legal dimensions of Ductile Cast Iron

*■ Ductile Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	275	305	350	26	2	12	φ25
250	345	380	430	28	2	12	φ27
300	395	430	480	30	3	16	φ27
350	440	480	540	34	3	16	φ33
400	495	540	605	38	3	16	φ33
450	560	605	675	40	3	20	φ33
500	615	660	730	42	3	20	φ33

*■ Ductile Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	266	295	340	20	3	12	φ23
250	319	355	405	22	3	12	φ28
300	370	410	460	24.5	4	12	φ28
350	429	470	520	26.5	4	16	φ28
400	480	525	580	28	4	16	φ31
450	548	585	640	30	4	20	φ31
500	609	650	715	31.5	4	20	φ34

DIMENSIONS - Dimension of Pump with Motor

C-6

■ 2P

units:mm

Model	Motor	Size		Pump								Motor					Common Base											Total		
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)
125X80CBJ	18.5	125	80	188	272	310	300	250	170	165	165	110	160L	345	329	255	125	170	430	160	650	-	970	370	330	4-φ19	77	3	1137	312
	22												180M	351.5	331.5	270	152										78	1146	340	
	30												200L	395.5	376.5	300	229										88	1235	427	
	37												225M	414.5	400.5	327	245										427			
	45												250M	482.5	434.5	373	307										443			
	55												280S	514	462	413	550										509			
150X100CBJ	37	150	100	202.5	327.5	340	310	280	200	175	185	170	200L	395.5	376.5	300	245	170	460	185	750	-	1120	440	400	4-φ19	94	4	1306	509
	45												225M	414.5	400.5	327	307										575			
	55												250M	482.5	434.5	373	378										675			
	75												280S	514	462	413	550										865			
	90												280M	539.5	487.5	413	570										891			
	110												315S	559	554	482	740										1105			
150X125CBH	22	150	125	210	335	360	330	290	180	185	175	170	180M	351.5	331.5	270	152	210	480	180	720	-	1080	400	360	4-φ19	92	3	1231	414
	30												200L	395.5	376.5	300	245										502			
	37												225M	414.5	400.5	327	307										518			
	45												250M	482.5	434.5	373	378										602			
	55												280S	514	462	413	550										686			
	75												315S	559	554	482	740										1105			
150X125CBJ	75	150	125	234	366	370	340	315	224	205	205	200	280S	514	462	413	550	210	510	225	910	-	1360	620	570	4-φ24	162	4	1580	912
	90												280M	539.5	487.5	413	570										938			
	110												315S	559	554	482	740										1120			
	132												315M	559	554	482	855										1310			
	160												315L	584.5	708.5	482	1080										1425			
	185												315L	584.5	708.5	482	1080										1535			
200X125CBH	45	200	125	221.5	348.5	385	340	265	215	200	200	190	225M	414.5	400.5	327	307	210	525	200	800	-	1200	500	450	4-φ24	130	4	1389	627
	55												250M	482.5	434.5	373	378										712			
	75												280S	514	462	413	550										906			
	90												280M	539.5	487.5	413	570										932			
	110												315S	559	554	482	740										1114			
	132												315L	584.5	708.5	482	1080										1114			

*1: The motor without size is high voltage motor, please contact us.

DIMENSIONS - Dimension of Pump with Motor

C-7

4P

Model	Motor	Size		Pump								Motor					Common Base										Total											
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)								
125X80CBJ	3	125	80	188	272	310	300	250	170	165	165	110	100L	193	197	177	34	170	410	125	500	-	750	330	290	4-φ15	46	3	853	190								
	4												112M	200	195	188.5	45										47		858	202								
	5.5												132S	239	241	212	61										48		943	219								
	7.5												132M	258	267	212	73										50		988	233								
125X80CBK	4	125	80	225	310	290	330	250	195	140	180	170	112M	200	195	188.5	45	190	390	135	550	-	820	360	320	4-φ15	50	3	933	265								
	5.5												132S	239	241	212	61										51		1018	282								
	7.5												132M	258	267	212	73										60		1063	303								
	11												160M	323	291	255	103			410	160	660	-	980	370	330	4-φ19		63	1152	336							
	15												160L	345	329	270	130												66	1212	366							
	18.5												180M	351.5	331.5	270	165												67	1221	402							
125X100CBK	7.5	125	100	245	370	345	370	280	230	180	200	240	132M	258	267	212	73	210	465	160	660	-	980	400	360	4-φ19	69	3	1143	382								
	11												160M	323	291	255	103										74		1232	417								
	15												160L	345	329	270	130										77		1292	447								
	18.5												180M	351.5	331.5	270	165			485	200	800	-	1200	440	390	4-φ24		76	1301	481							
	22												180L	370.5	347.5	270	180												79	1336	499							
	30												200L	395.5	376.5	300	238												99	1391	577							
	37												225S	432	388	327	298												103	1439	641							
150X100CBJ	4	150	100	202.5	327.5	340	310	280	200	175	185	170	112M	200	195	188.5	45	170	440	135	540	-	810	330	290	4-φ15	49	3	928	264								
	5.5												132S	239	241	212	61										51		1013	282								
	7.5												132M	258	267	212	73		460	150	600	-	900	370	330	4-φ19	59		1058	302								
	11												160M	323	291	255	103										65		1147	338								
	15												160L	345	329	255	130		500	195	780	-	1170	440	400	4-φ19	86		3	1352	526							
	18.5												180M	351.5	331.5	270	165										104		1396	594								
	22												180L	370.5	347.5	270	180										109		1451	657								
	30												200L	395.5	376.5	300	238		520	210	840	-	1260	500	450	4-φ24	113		4	1499	721							
	37												225S	432	388	327	298										115		1524	747								
	45												225M	444.5	400.5	327	322										127		1596	847								
55	250M	482.5	434.5	373	410	225	920	-	1370	560	510	145	1655	1010																								
150X125CBH	4	150	125	210	335	360	330	290	180	185	175	170	280S	514	462	413	555	210	480	140	580	-	860	400	360	4-φ19	66	3	943	281								
	5.5												132S	239	241	212	61										67		1028	298								
	7.5												132M	258	267	212	73										70		1073	313								
150X125CBJ	7.5	150	125	234	366	370	340	315	224	205	205	200	132M	258	267	212	73	210	490	160	660	-	980	400	360	4-φ19	71	3	1128	344								
	11												160M	323	291	255	103										76		1217	379								
	15												160L	345	329	270	130										79		1277	409								
	18.5												180M	351.5	331.5	270	165			81	1286	444																
	22												180L	370.5	347.5	270	180			81	1321	461																
150X150CBG	4	150	150	225	320	350	305	275	170	175	165	150	112M	200	195	188.5	45	210	450	140	570	-	850	400	360	4-φ15	58	3	943	253								
	5.5												132S	239	241	212	61										66		1028	277								
	7.5												132M	258	267	212	73		470	145	600	-	890	400														
	22												180L	370.5	347.5	270	180		260	570	210	840	-	1260	490	440	500		450	4-φ24	118	3	1426.5	728				
	30												200L	395.5	376.5	300	238														124	1481.5	792					
	37												225S	432	388	327	298														125	1529.5	853					
	45												225M	444.5	400.5	327	322														128	1554.5	880					
55	250M	482.5	434.5	373	410	140	1626.5	980																														
75	280S	514	462	413	555	162	1685.5	1147																														
200X100CBK	90	200	100	285	420.5	430	465	350	275	185	255	430	280M	539.5	487.5	413	610	235	490	160	660	-	980	440	400	4-φ19	76	3	1133	359								
	110												315S	589	554	482	750										610		260	1050	-	1570	700	640	4-φ26	227	1852.5	1407
	220X125CBH												5.5	132S	239	241	212										61		69	1053	320							
	7.5												132M	258	267	212	73			72	1098	335																
	11												160M	323	291	255	103			77	1187	370																
	15												160L	345	329	270	130			80	1247	400																
	200X125CBJ												15	200	125	221.5	348.5			405	400	280	240	210	230	240	160L		345	329	255	130	210	525	180	730	-	1090
18.5		180M	351.5	331.5	270	165	84	1291	504																													
22		180L	370.5	347.5	270	180	91	1346	569																													
30		200L	395.5	376.5	300	238	112	1394	650																													
37		225S	432	388	327	298	545	200	800	-	1200	500	450					4-φ24	122								4	1504	824									
200X150CBG	7.5	200	150	255	350	370	330	285	205	185	185	210	132M	258	267	212	73	235	490	160	660	-	980	440	400	4-φ19	76	3	1133	359								
	11												160M	323	291	255	103										81		1222	394								
	15												160L	345	329	270	130										84		1282	424								
200X150CBH	11	200	150	242.5	352.5	395	380	260	240	210	220	260	160M	323	291	255	103	235	515	175	720	-	1070	440	400	4-φ19	83	3	1212	446								
	15												160L	345	329	270	130										87		1272	477								
	18.5												180M	351.5	331.5	270	165										86		1281	511								
	22												180L	370.5	347.5	270	180										89		1316	529								
200X150CBJ	22	200	150	265.5	389.5	425	405	390	275	230	260	380	180L	370.5	347.5	270	180	235	565	200	800	-	1200	440	390	4-φ24	110	3	1376	670								
	30												200L	395.5	376.5	300	238										115		1431	733								
	37												225S	432	388	327	298										120		1479	798								
	45												225M	444.5	400.5	327	322			122	1504	824																
	55												250M	482.5	434.5	373	410			135	1576	925																
	75												280S	514	462	413	555			156	1635	1091																

DIMENSIONS - Dimension of Pump with Motor

C-8

4P																														units:mm																					
Model	Motor	Size		Pump								Motor					Common Base										Total																								
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)																					
200X200CBF	5.5	200	200	245	340	385	380	320	210	200	200	230	132S	239	241	212	61	235	505	155	620	-	930	440	400	4-φ19	74	3	1068	365																					
	7.5												132M	258	267	212	73										77			380																					
	11												160M	323	291	255	103										82			415																					
250X150CBH	18.5	250	150	272	408	460	425	290	264	230	250	340	180M	351.5	331.5	270	165	260	600	200	800	-	1200	490	440	4-φ24	118	3	1366	623																					
	22												180L	370.5	347.5	270	180										122			1401	642																				
	30												200L	395.5	376.5	300	238										128			1456	706																				
	37												225S	432	388	327	298										129	1504	767																						
	45												225M	444.5	400.5	322	322										132	1529	794																						
250X150CBJ	45	250	150	294	451	480	450	440	310	250	290	470	225M	444.5	400.5	327	322	260	620	230	920	-	1380	500	510	4-φ24	136	4	1594	928																					
	55												250M	482.5	434.5	373	410										150			1666	1030																				
	75												280S	514	462	413	555										175			1725	1200																				
	90												280M	539.5	487.5	610	225										1776	1305																							
	110												315S	589	554	482	750										243	1892	1463																						
250X150CBK	37	250	150	345	520	480	520	390	310	205	285	630	225S	432	388	327	298	295	620	240	980	-	1460	560	510	4-φ24	145	4	1689	1073																					
	45												225M	444.5	400.5	322	322										148			1714	1100																				
	55												250M	482.5	434.5	373	410										157			1786	1197																				
	75												280S	514	462	413	555										227			1845	1412																				
	90												280M	539.5	487.5	610	234										1896	1474																							
	110												315S	589	554	750	265										2012	1645																							
	132												315M			875	272										1777																								
	160												315L	614.5	708.5	482	960										273	2192	1863																						
	185															1070												1973																							
250X200CBF	11	250	200	275	390	450	395	315	243	225	225	320	160M	323	291		103	260	570	185	760	-	1130	490	450	4-φ19	95	3	1282	518																					
	15												160L	345	329	255	130										116			1342	566																				
	18.5												180M	351.5	331.5		165																																		
250X200CBGX	15	250	200	270	385	435	370	300	225	210	210	270	180L	370.5	347.5	270	180	260	575	195	780	-	1170	490	440	4-φ24	114	3	1332	514																					
	22												200L	395.5	376.5		238										118			1376	568																				
	30												220L	420	380		280										133			1426	653																				
250X200CBGY	37	250	200	290	415	475	415	340	250	235	235	340	200L	395.5	376.5	300	238	295	615	210	860	-	1280	560	510	4-φ24	133	4	1481	717																					
	45												225S	432	388	327	298										141			1529	779																				
	55												225M	444.5	400.5	322	322										144			1554	806																				
	75												280L	514	462		555										144			1481	852																				
250X200CBH	37	250	200	284.5	420.5	505	475	350	280	260	280	470	225S	432	388	327	298	295	645	220	890	-	1330	560	510	4-φ24	146	4	1529	914																					
	45												225M	444.5	400.5	322	322										149			1554	941																				
	55												250M	482.5	434.5	373	410										159			1626	1039																				
	75												280S	514	462	413	555										186			1685	1211																				
	90												280M	539.5	487.5	610	229										1865	1644																							
300X150CBK	110	300	150	350	535	485	600	440	345	235	320	860	315S	589	554		750	295	665	305	1220	-	1830	700	640	4-φ26	236	4	1916	1706																					
	132												280M	539.5	487.5	610	275										2032			1877																					
	160												315M			875	274										2009																								
	185												315L	614.5	708.5	482	960										275			2212	2095																				
	200															1070												2205																							
	220															1080												2215																							
	250															1630												2808																							
	280															1640												2818																							
	315															1690												2868																							
	355*1															1790												2968																							
	*1																																																		
	300X200CBG												45	300	200	310	460										525	465	355	270	260	265	580	225M	444.5	400.5	327	322	295	645	240	950	-	1430	560	530	4-φ19	151	4	1619	1077
													55																					250M	482.5	434.5	373	410										155			1691
75		280S	514	462	413	555	165	1750	1340																																										
300X200CBH	55	300	200	310	490	560	535	405	320	295	315	690	250M	482.5	434.5	373	410	295	700	250	1020	-	1520	560	510	4-φ24	171	4	1721	1271																					
	75												280S	514	462	413	555										246			1780	1491																				
	90												280M	539.5	487.5	610	270										1831			1554																					
	110												315S	589	554	750	280										1947			1713																					
	132												315M	614.5	708.5	482	875										296	2127	1861																						
300X200CBJX	75	300	200	321	480	545	505	495	336	280	320	720	280S	514	462	413	555	295	725	260	1040	-	1560	620	560	4-φ26	243	4	1781	1518																					
	90												280M	539.5	487.5	610	265										1832			1581																					
	110												315S	589	554	750	275										1948			1740																					
	132												315M			875	293										1888																								
	160												315L	614.5	708.5	482	960										294	2128	1974																						
	185															1070												2084																							
300X200CBJY	132	300	200	349	526	565	565	550	374	315	360	870	315M				875	295	745								4-φ26	299	4	2202	2044																				
	160												315L	614.5	708.5	482	960											300			2130	2240																			
	185															1070															2250																				
	200															1080															2847																				
	220															1630													2857																						
	250															1640													2907																						
	315															1790													3007																						
*1																																																			

DIMENSIONS - Dimension of Pump with Motor

C-9

4P

units:mm

Model	Motor	Size		Pump								Motor					Common Base										Total															
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)												
300X250CBFX	18.5	300	250	280	415	505	445	350	265	255	255	480	180M	351.5	331.5	270	165	295	645	205	840	-	1250	560	510	4-φ24	133	3	1381	778												
	22												180L	370.5	347.5	270	180			210	860	-	1280				137		1416	797												
	30												200L	395.5	376.5	300	238			220	890	-	1330				144		1471	862												
300X250CBFY	30	300	250	335	460	520	495	355	300	275	285	590	200L	395.5	376.5	300	238	295	665	225	920	-	1370	560	510	4-φ24	154	4	1571	982												
	37												225S	432	388	327	298			230	940	-	1400				156		1619	1044												
	45												225M	444.5	400.5	322	322			235	950	-	1420				159		1644	1071												
	55												250M	482.5	434.5	373	410			245	1000	-	1490				170		1716	1170												
300X250CBG	75	300	250	370	525	600	560	450	305	307	300	780	280S	514	462	413	555	330	745	280	1080	-	1640	740	700	4-φ24	214	4	1875	1589												
	90												280M	539.5	487.5	410	610			290	1110	-	1690				217		1926	1655												
	110												315S	589	554	482	750			300	1145	-	1745				220		2042	1800												
	132												315M	614.5	708.5	482	875			310	1230	-	1850				226		2222	1931												
300X250CBH	110	300	250	350	535	625	600	450	355	340	355	860	315S	589	554	482	750	330	810	290	1180	-	1760	740	680	4-φ26	347	4	2032	1957												
	132												315M	614.5	708.5	482	875										358		2093													
	160												315L	614.5	708.5	482	960												359		2179											
	185																														2289											
	200																														2299											
	220																														2900											
350X250CBG	132	350	250	390	570	585	440	340	270	335	890	890	315M	704	816	646	1630	330	730	330	1260	-	1920	830	770	6-φ26	410	5	2410	2900												
	160												315L	614.5	708.5	482	875										2045															
	185												315L	614.5	708.5	482	960												359		2148											
	200																														2258											
	220																														2268											
350X250CBH	185	350	250	365	555	665	675	500	395	270	395	1180	355M	704	816	646	1630	420	850	330	1320	-	1980	840	770	6-φ26	409	5	2485	3033												
	200												315L	614.5	708.5	482	1070												401		2651											
	220																														2661											
	250																														3333											
	280												355M	704	816	646	1640										3343															
	315												355L	704	816	646	1690										3393															
	355*1												*1																		3493											
	400*1												*1																		3493											
350X250CBJ	220	350	250	394.5	620.5	645	635	615	420	335	405	1240	355M	704	816	646	1630	370	870	215	1720	860	2150	830	760	6-φ28	525	5	2540	3395												
	250												355L	704	816	646	1690										3405															
	280												315L	614.5	708.5	482	1070													401		3455										
	315																															3555										
	355*1																															3555										
	400*1																															3555										
350X300CBF	55	350	300	360	510	600	560	450	330	275	320	830	250M	482.5	434.5	373	410	330	745	270	1055	-	1595	740	700	4-φ24	216	4	1791	1496												
	75												280S	514	462	413	555			280	1085	-	1645				219		1850	1644												
	90												280M	539.5	487.5	410	610			290	1115	-	1695				222		1901	1710												
	220												355M	704	816	646	1630			3565																						
400X300CBG	220	400	300	440	630	625	660	510	380	310	375	1400	355M	704	816	646	1640	425	810	390	1555	777.5	2335	810	740	6-φ26	431	5	2595	3575												
	250												355L	704	816	646	1690										3625															
	280												*1																		3725											
	315												*1																		3725											
400X300CBH	315	400	300	450	685	715	755	515	445	320	445	1670	355L	704	816	646	1790	420	940	225	1820	910	2270	840	770	6-φ28	576	5	2660	4036												
	355*1												*1																		4036											
	400*1												*1																		4036											
	450*1												*1																		4036											
	500*1												*1																		4036											
	630*1												*1																		4036											
400X300CBJX	400*1	400	300	559	756	725	710	690	470	380	455	1940	*1																		4036											
	450*1												*1																		4036											
	500*1												*1																		4036											
	630*1												*1																		4036											
	800*1												*1																		4036											
400X350CBF	90	400	350	420	575	645	625	510	370	321	360	1050	280M	539.5	487.5	413	610	375	790	300	1185	-	1785	750	710	4-φ24	224	4	2026	1932												
	110												315S	589	554	482	750			310	1220	-	1840				227		2142	2077												
	132												315M	614.5	708.5	482	875			330	1285	-	1945				233		2322	2208												
	160												315L	614.5	708.5	482	875			330	1285	-	1945				233		2322	2208												
400X400CBF	160	400	400	470	645	725	690	505	410	380	405	1550	315L	614.5	708.5	482	1070	455	915	360	1425	712.5	2145	850	780	6-φ26	424	4	2442	3112												
	185												355M	704	816	646	1080												439		3122											
	200																														3723											
	220																														3733											
	250												355L	704	816	646	1640														3783											
	280												*1																		3883											
	315												*1																		3883											

DIMENSIONS - Dimension of Pump with Motor

C-10

■ 6P

units:mm


Model	Motor		Size		Pump							Motor					Common Base											Total							
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)					
350X250CBH	30	350	250	365	555	665	675	500	395	270	395	1180	225M	444.5	400.5	327	294	420	850		270	1100	-	1640	840	780	4-φ26	354	4		1769	1828			
	37												250M	482.5	434.5	373	394			285	1140	-	1710	371				1841		1945					
	45												280S	514	462		510			290	1180	-	1760	421				1900		2111					
	55												280M	539.5	487.5		535			300	1210	-	1810	432				1951		2147					
	75												315S	589	554		680			310	1250	-	1870	447				2067		2307					
	90												315M	614.5	708.5		482			835	330	1320	-	1980				479		2247	2494				
	110												315L				975							481				2267		2636					
350X250CBJ	55	350	250	394.5	620.5	645	635	615	420	335	405	1240	280M	539.5	487.5	413	535	370	830		305	1220	-	1830	740	680	4-φ26	421	5		2047	2196			
	75												315S	589	554		680			315	1260	-	1890	437				2163		2357					
	90												315M				835					-						2525							
	110															975					-		1990					2665							
	132												315L	614.5	708.5		482			1030								2720							
	160																1630											3500							
	185												355M	704	816	646				1760										3630					
400X300CBG	45	400	300	440	630	625	660	510	380	310	375	1400	280S	514	462	413	510	420	810		305	1220	-	1830	740	680	4-φ26	398	4		2050	2308			
	55												280M	539.5	487.5		535			315	1260	-	1890	408				2101		2343					
	75												315S	589	554		680			320	1300	-	1940	439				2217		2519					
	90												315M	614.5	708.5		482			835	205	1640	820	2050						6-φ26	457	2397	2692		
	110												315L				975											2832							
400X300CBH	55	400	300	450	685	715	755	515	445	320	445	1670	280M	539.5	487.5	413	535	420	900		320	1300	-	1940	840	780	4-φ26	475	5		2167	2680			
	75												315S	589	554		680			330	1340	-	2000	493				2283		2843					
	90												315M				835											3162							
	110												315L	614.5	708.5		482			975	205	1700	850	2110				657		2463	3302				
	132																1030											3357							
	160																1630											3991							
	185												355M	704	816	646				1760	225	1820	910	2270				691		2660	4121				
400X300CBJX	90	400	300	559	756	725	710	690	470	380	455	1940	315M				835	420	950						840	770	6-φ28		5			3442			
	110															975					210	1760	880	2180				667		2643	3582				
	132												315L	614.5	708.5		482			1030								3637							
	160																1630											4272							
	185																1760											4402							
	200																1870											4512							
	220												355L				1950											4592							
400X300CBJY	160	400	300	432	658	815	800	630	515	420	510	1260					1630	450	1045	225	1820	910	2270	940	870	6-φ28	804	5	2615		3694				
	185															1760																			3824
	200												355M	704	816	646														1870					3934
	220												355L				1950																		4014
	250																																		
	280																																		
	315																																		
400X400CBF	37	400	400	470	645	725	690	505	410	380	405	1550	250M	482.5	434.5	373	394	450	915		305	1220	-	1830	840	780	4-φ26	420	4		2036	2364			
	45												280S	514	462		510			310	1260	-	1880	475				2095		2535					
	55												280M	539.5	487.5		535			320	1290	-	1930	486				2146		2571					
	75												315S	589	554	482	680			330	1330	-	1990	504				2262		2734					
	90												315M				835											2953							
	110																975					205	1720	860				2130				718	4	2482	3093
	132												315L	614.5	708.5		482			1030								3148							
450X300CBH	160	450	300	475.5	679.5	800	800	580	490	380	500	1400	355M				1630	450	1030					900	830	6-φ28		5		2680	3917				
	185															1760													3947						
	200																												4057						
	220																												4137						
	250												355L				1870																		
	280																1950																		
	315																																		
355																																			

*1: The motor without size is high voltage motor, please contact us.

*1

CONSTRUCTION - Sectional View of Pump

D-1



Mechanical Seal Type

No	Part Name	GB Material	JIS Material	Qty
053-2	Bearing Cover	HT250	FC250	1
053-1	Bearing Cover	HT250	FC250	1
051-2	Bearing Unit	HT200	FC200	1
051-1	Bearing Unit	HT200	FC200	1
045	O-ring	NBR	NBR	2
041	Impeller Nut	ZCuSn5Pb5Zn5	CAC406	1
039-2	Coupling Key	50	S50C	1
039-1	Impeller Key	20Cr13	SUS420J1	1
031	Shaft	20Cr13	SUS420J1	1
021	Impeller	ZCuSn5Pb5Zn5 (or ZG0Cr18Ni9) ^{*2}	CAC406 (or SCS13) ^{*2}	1
011-2	Side Cover	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
011-1	Side Cover	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
006	Casing Lower Half	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
004	Casing Upper Half	T250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1

No	Part Name	GB Material	JIS Material	Qty
162-3	Plug1"	Q235-A	SS	1
162-2	Plug1/2"	Q235-A	SS	1
162-1	Plug3/8"	Q235-A	SS	2
156	Lock Pin	06Cr19Ni10	SUS304	2
136	Bearing Washer	Q235-A	SS	1
129	Bearing Nut	Q235-A	SS	1
117-1	Gasket (Casing)	-	Fiber Materials	1
111-2	Mechanical Seal	-	-	1
111-1	Mechanical Seal	-	-	1
107-2	Casing Wear Ring	ZCuSn5Pb5Zn5	CAC406	1
107-1	Casing Wear Ring	ZCuSn5Pb5Zn5	CAC406	1
093-2	Deflector (CCP Side)	NBR	NBR	1
093-1	Deflector (CP Side)	NBR	NBR	1


*1: The material is changed to ductile cast iron for model 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH.

*2: The material is changed to cast stainless steel for model 400X300CBJX, 400X300CBJY, 450X300CBH, 450X350CBG, 450X350CBJ, 450X400CBF, 500X350CBG, 500X350CBH.

CONSTRUCTION - Sectional View of Mechanical Seal


D-2

Standard shaft seal (16 bar) : Type 2100 / Diameter of axle < 100mm




Part No.	Part Name	Material	Qty/unit
1	Bellows	NBR	1
2	Primary Ring	Carbon	1
3	Drive Band	316 Stainless Steel	1
4	Spring	316 Stainless Steel	1
5	O-ring	NBR	1
6	Mating Ring	Ceramic	1

Standard shaft seal (16 bar) : Type 8-1 / Diameter of axle > 100mm



Part No.	Part Name	Material	Qty/unit
1	Retainer	316 Stainless Steel	1
2	Holding screw	316 Stainless Steel	1
3	Spring	316 Stainless Steel	1
4	O-ring	FPM	1
5	Primary Ring	Carbon	1
6	Mating Ring	Silicon carbide	1
7	O-ring	FPM	1
8	Pin	304 Stainless Steel	1

50Hz - 2P




Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity 1.0mPa · s.

Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

50Hz - 4P




Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity $1.0\text{mPa} \cdot \text{s}$.

Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

50Hz - 6P



Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity 1.0mPa · s.


Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

Performance Curve

2 Poles



F8-1932880-00


Performance Curve

2 Poles

150X100CBJ

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 2970 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932881-00


Performance Curve

2 Poles

150X125CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 2940 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932882-00

Performance Curve

2 Poles



F8-1932883-00


Performance Curve

2 Poles

200X125CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 2970 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932884-00

Performance Curve


4 Poles



S8-1738863-01

Performance Curve


4 Poles



S8-1738882-00

Performance Curve


4 Poles



S8-1738883-00

Performance Curve

4 Poles



S8-1738864-01


Performance Curve

4 Poles

150X100CBK

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1485 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738884-00

Performance Curve


4 Poles



S8-1738873-00

Performance Curve


4 Poles



S8-1738865-01

Performance Curve


4 Poles



S8-1738888-00

Performance Curve

4 Poles



S8-1738885-00


Performance Curve

4 Poles

200X125CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738874-00


Performance Curve

4 Poles

200X125CBJ

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738866-01


Performance Curve

4 Poles

200x150CBG

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738889-00

Performance Curve


4 Poles



S8-1738875-00

Performance Curve


4 Poles



S8-1738867-01

Performance Curve


4 Poles



S8-1738892-00

Performance Curve


4 Poles



S8-1738876-00

Performance Curve

4 Poles



S8-1738868-01


Performance Curve

4 Poles

250X150CBK

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738886-00


Performance Curve

4 Poles

250X200CBF

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738893-00


Performance Curve

4 Poles

250X200CBGX

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738890-00


Performance Curve

4 Poles

250X200CBGY

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1485 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738891-00


Performance Curve

4 Poles

250X200CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1485 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738877-00


Performance Curve

4 Poles

300X150CBK

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738887-00

Performance Curve


4 Poles



S8-1734506-00

Performance Curve


4 Poles



S8-1738878-01

Performance Curve


4 Poles



S8-1738869-01

Performance Curve


4 Poles



S8-1738870-01

Performance Curve

4 Poles



S8-1738894-00


Performance Curve

4 Poles

300X250CBFY

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1470 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738895-00


Performance Curve

4 Poles

300X250CBG

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1734507-00

Performance Curve

4 Poles



S8-1738879-00


Performance Curve

4 Poles

350X250CBG

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1734508-00

Performance Curve


4 Poles



S8-1738880-00

Performance Curve


4 Poles



S8-1738871-01

Performance Curve

4 Poles



S8-1734509-00


Performance Curve

4 Poles

400X300CBG

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1734510-00

Performance Curve

4 Poles



S8-1738881-00


Performance Curve

4 Poles

400X300CBJX

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1738872-01


Performance Curve

4 Poles

400X350CBF

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 1490 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1734511-00

Performance Curve


4 Poles



S8-1734512-00

Performance Curve

6 Poles



F8-1932885-00


Performance Curve

6 Poles

350X250CBJ

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min^{-1})


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932886-00

Performance Curve

6 Poles



F8-1932887-00


Performance Curve

6 Poles

400X300CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min^{-1})

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932888-00


Performance Curve

6 Poles

400X300CBJX

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932889-00


Performance Curve

6 Poles

400X300CBJY

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min^{-1})


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932890-00

Performance Curve

6 Poles



F8-1932891-00


Performance Curve

6 Poles

450X300CBH

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min^{-1})


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932892-00

Performance Curve

6 Poles



F8-1932893-00


Performance Curve

6 Poles

450X350CBJ

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 990 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932894-00


Performance Curve

6 Poles

450X400CBF

According to ISO testing
code 9906 Grade 2B Class 250 Hz (Speed 985 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932895-00

Performance Curve

6 Poles




F8-1932896-00

Performance Curve

6 Poles

500X350CBH	According to ISO testing code 9906 Grade 2B Class 2
50 Hz (Speed 990 min ⁻¹)	DENSITY= 1.0 kg/l, VISCOSITY= 1.0 mPa.s



F8-1932897-00