




TECHNICAL DATA BOOK

CB HORIZONTAL SPLIT CASING PUMP

60HZ



SPECIFICATION

Main Applications and Product Features	A-1
Model Code	A-2
Specification	A-3

TECHNICAL DATA

Impeller Diameter	B-1
Noise Data	B-2
Nominal Dimension of Parts	B-3

DIMENSIONS

Dimensions of Bare Shaft Pump	C-1, 2, 3, 4
Dimensions of Pump with motor	C-5, 6, 7, 8, 9, 10, 11

CONSTRUCTION

Sectional View of Pump	D-1
Selection View of Mechanical Seal	D-2

SELECTION CHART

50Hz m ³ /min · m – 2P, 4P, 6P	E-1, 2, 3
---	-----------

PERFORMANCE CURVES**50Hz – 2P**

125X80 CBJ , 150X100 CBJ , 150X125 CBH , 150X125 CBJ , 200X125 CBH

50Hz – 4P

125X80 CBJ , 125X80 CBK , 125X100 CBK , 150X100 CBJ , 150X100 CBK ,
 150X125 CBH , 150X125 CBJ , 150X150 CBG , 200X100 CBK , 200X125 CBH ,
 200X125 CBJ , 200X150 CBG , 200X150 CBH , 200X150 CBJ , 200X200 CBF ,
 250X150 CBH , 250X150 CBJ , 250X150 CBK , 250X200 CBF , 250X200 CBGX ,
 250X200 CBGY , 250X200 CBH , 300X150 CBK , 300X200 CBG , 300X200 CBH ,
 300X200 CBJX , 300X200 CBJY , 300X250 CBFX , 300X250 CBFY , 300X250 CBG ,
 300X250 CBH , 350X250 CBG , 350X250 CBH , 350X250 CBJ , 350X300 CBF ,
 400X300 CBG , 400X300 CBH , 400X300 CBJX , 400X350 CBF , 400X400 CBF

50Hz – 6P

350X250 CBH , 350X250 CBJ , 400X300 CBG , 400X300 CBH , 400X300 CBJX ,
 400X300 CBJY , 400X400 CBF , 450X300 CBH , 450X350 CBG , 450X350 CBJ ,
 450X400 CBF , 500X350 CBG , 500X350 CBH

Main Applications

Water Supply

- Water supply duties for municipalities
- Irrigation (flooding, sprinkler, farming)
- Drainage clean water

General Industrial Systems

- Water supply
- Process cooling and chilled water systems
- Cooling systems and water condensing systems
- Water circulation
- Boiler feed systems

Building

- General water supply
- Air conditioning
- Water condensing systems
- Fire protection



Product Features

Energy-saving Design

- World top class pump efficiency achieved.
- Major improvement over our previous models by impeller designed using our proprietary 3D inverse design technology.
- Higher efficiency means lower energy consumption and motor output, and more compact size.

Simple Maintenance

- Very compact design for ease of installation and permits minimum maintenance.
- Axially split casing allows the easy removal of the top casing for inspection and service.
- Shield bearings eliminate need for adding or exchanging lubricating oil.
- Shaft seal flushing and quenching piping not required for the standard application.



SPECIFICATION - General Description

A-3

Pump specification

Capacities		To 62 m ³ /min (60Hz)
Heads		To 150 m (60Hz)
Liquid Handled	Type of liquid	Clean water, Industrial water, River water
	Temperature	0 to 80°C
Max. Operating Pressure		16bar (1.6MPa)
Construction	Impeller	Closed double suction
	Shaft seal	Mechanical Seal
	Flushing	No Flushing
	Ball Bearing	Sealed ball bearing (grease lubrication)
Flange		JIS 16K RF, GB PN16 RF
Material	Casing	FC250 or FCD450 *1
	Impeller	CAC406 or SCS13 *2
	Main shaft	SUS420J1
	Mechanical Seal	Ceramic/Carbon NBR or Silicon carbide/Carbon FPM *3

*1: It is applicable for Model 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG

*2: It is applicable for Model 400X300CBJX, 400X300CBJY, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG

*3: It is applicable for Model 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY

Motor specification

Number of poles	4 poles	6 poles
Synchronous speed	1800min ⁻¹	1200min ⁻¹
Phase	3 Phase	
Voltage	380V ±10%	
Type	Totally enclosed fan cooled (indoors)	
Protection	IP55	
Frequency	30~60Hz	

* Optional:

1. Totally enclosed fan cooled (indoors)
2. Varying frequency running (5~60Hz)
3. Other types of motor that user require

Accessories**Standard:**

- Common base
- Coupling
- Coupling guard

Optional:

- Disc coupling

TECHNICAL DATA - Impeller Diameter

B-1

— Not applicable Model Unit : mm

Model				
	4P		6P	
	Max	Min	Max	Min
125X80CBJ	228	191	—	—
125X80CBK	292	234	—	—
125X100CBK	328	262	—	—
150X100CBJ	255	214	—	—
150X100CBK	368	294	—	—
150X125CBH	216	166	—	—
150X125CBJ	286	239	—	—
150X150CBG	196	165	—	—
200X100CBK	413	330	—	—
200X125CBH	242	186	—	—
200X125CBJ	319	267	—	—
200X150CBG	220	185	—	—
200X150CBH	272	209	—	—
200X150CBJ	357	299	—	—
200X200CBF	197	165	—	—
250X150CBH	306	235	—	—
250X150CBJ	401	336	—	—
250X150CBK	463	370	—	—
250X200CBF	221	185	—	—
250X200CBGX	247	207	—	—
250X200CBGY	277	233	—	—
250X200CBH	343	264	—	—
300X150CBK	521	416	—	—
300X200CBG	311	261	—	—
300X200CBH	386	296	—	—
300X200CBJX	448	376	—	—
300X200CBJY	503	421	—	—
300X250CBFX	247	208	—	—
300X250CBFY	277	232	—	—
300X250CBG	349	293	—	—
300X250CBH	432	332	—	—
350X250CBG	392	329	—	—
350X250CBH	486	373	486	373
350X250CBJ	—	—	563	472
350X300CBF	311	261	—	—
400X300CBG	440	369	440	369
400X300CBH	—	—	544	418
400X300CBJX	—	—	631	528
400X300CBJY	—	—	707	593
400X350CBF	349	293	—	—
400X400CBF	—	—	391	328
450X300CBH	—	—	612	470
450X350CBG	—	—	494	414
450X400CBF	—	—	439	370
500X350CBG	—	—	555	465

TECHNICAL DATA - Noise Data

B-2

— Not applicable Model Unit : dB(A)

Model	60Hz	
	4P	6P
125X80CBJ	73	—
125X80CBK	76	—
125X100CBK	78	—
150X100CBJ	75	—
150X100CBK	79	—
150X125CBH	73	—
150X125CBJ	76	—
150X150CBG	74	—
200X100CBK	80	—
200X125CBH	75	—
200X125CBJ	78	—
200X150CBG	75	—
200X150CBH	76	—
200X150CBJ	79	—
200X200CBF	74	—
250X150CBH	78	—
250X150CBJ	80	—
250X150CBK	81	—
250X200CBF	76	—
250X200CBGX	76	—
250X200CBGY	78	—
250X200CBH	79	—
300X150CBK	83	—
300X200CBG	79	—
300X200CBH	80	—
300X200CBJX	82	—
300X200CBJY	83	—
300X250CBFX	77	—
300X250CBFY	79	—
300X250CBG	81	—
300X250CBH	82	—
350X250CBG	82	—
350X250CBH	83	80
350X250CBJ	—	81
350X300CBF	80	—
400X300CBG	84	80
400X300CBH	—	82
400X300CBJX	—	83
400X300CBJY	—	84
400X350CBF	81	—
400X400CBF	—	79
450X300CBH	—	82
450X350CBG	—	82
450X400CBF	—	81
500X350CBG	—	84

Note : The overall sound pressure level is the value measured 1m away from the pump unit and does not include driver noise.

This data is for reference and may differ from the actual noise level.

TECHNICAL DATA - Nominal Dimension of Parts



B-3

Model	Shaft Diameter (mm)	At Radial Bearing	At Thrust Bearing	CP side Mechanical Seal	CCP side Mechanical Seal
125X80CBJ	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
125X80CBK	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
125X100CBK	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X100CBJ	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X100CBK	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
150X125CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
150X125CBJ	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
150X150CBG	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X100CBK	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
200X125CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
200X125CBJ	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
200X150CBG	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X150CBH	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
200X150CBJ	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
200X200CBF	28	UCFC206FC	UCFC206FD	0350 / T 2100	0350 / T 2100
250X150CBH	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X150CBJ	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
250X150CBK	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
250X200CBF	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X200CBGX	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
250X200CBGY	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
250X200CBH	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X150CBK	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X200CBG	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X200CBH	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
300X200CBJX	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X200CBJY	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
300X250CBFX	38	UCFC208FC	UCFC206FD	0450 / T 2100	0350 / T 2100
300X250CBFY	48	UCFC210FC	UCFC208FD	0550 / T 2100	0450 / T 2100
300X250CBG	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
300X250CBH	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
350X250CBG	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
350X250CBH	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
350X250CBJ	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
350X300CBF	55	UCFC212FC	UCFC210FD	0650 / T 2100	0550 / T 2100
400X300CBG	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100
400X300CBH	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
400X300CBJX	105	UCFS322C	UCFS320FD	1174 / T 8-1	1079 / T 8-1
400X300CBJY	95	UCFCX20C	UCFC218FD	1047 / T 8-1	0950 / T 2100
400X350CBF	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
400X400CBF	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
450X300CBH	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100
450X350CBG	75	UCFC216FC	UCFC214FD	0850 / T 2100	0750 / T 2100
450X400CBF	65	UCFC214FC	UCFC212FD	0750 / T 2100	0650 / T 2100
500X350CBG	85	UCFC218FC	UCFC216FD	0950 / T 2100	0850 / T 2100


DIMENSIONS - Dimensions of Bare Shaft Pump

C-1


PUMP



Shaft end



Flange



■ Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	24	2	8	Ø23
100	160	185	225	26	2	8	Ø23
125	195	225	270	26	2	8	Ø25
150	230	260	305	28	2	12	Ø25
* 200	275	305	350	30	2	12	Ø25
* 250	345	380	430	34	2	12	Ø27
* 300	395	430	480	36	3	16	Ø27
* 350	440	480	540	38	3	16	Ø33
* 400	495	540	605	42	3	16	Ø33
* 450	560	605	675	46	3	20	Ø33
* 500	615	660	730	50	3	20	Ø33

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG
use the legal dimensions of Ductile Cast Iron

■ Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	22	3	8	Ø19
100	156	180	220	24	3	8	Ø19
125	184	210	250	26	3	8	Ø19
150	211	240	285	26	3	8	Ø23
* 200	266	295	340	30	3	12	Ø23
* 250	319	355	405	32	3	12	Ø28
* 300	370	410	460	32	4	12	Ø28
* 350	429	470	520	36	4	16	Ø28
* 400	480	525	580	38	4	16	Ø31
* 450	548	585	640	40	4	20	Ø31
* 500	609	650	715	42	4	20	Ø34

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG
use the legal dimensions of Ductile Cast Iron

*■ Ductile Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	275	305	350	26	2	12	Ø25
250	345	380	430	28	2	12	Ø27
300	395	430	480	30	3	16	Ø27
350	440	480	540	34	3	16	Ø33
400	495	540	605	38	3	16	Ø33
450	560	605	675	40	3	20	Ø33
500	615	660	730	42	3	20	Ø33

*■ Ductile Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	266	295	340	20	3	12	Ø23
250	319	355	405	22	3	12	Ø28
300	370	410	460	24.5	4	12	Ø28
350	429	470	520	26.5	4	16	Ø28
400	480	525	580	28	4	16	Ø31
450	548	585	640	30	4	20	Ø31
500	609	650	715	31.5	4	20	Ø34

DIMENSIONS - Dimensions of Bare Shaft Pump

C-2

■ 4P

Units:mm

MODEL	Size		Pump																Shaft						Wt (KG)
	Ds	Dd	A	B	C	E	F	G	H	I	J	K	M	N	O	P	Q	Z	L	R	T	U	V	W	
125X80CBJ	125	80	188	272	310	300	250	170	165	165	60	70	300	290	250	230	20	19	56	60.1	28	8	5	10	110
125X80CBK	125	80	225	310	290	330	250	195	140	180	70	80	340	320	280	250	20	19	63	70	28	8	5	10	170
125X100CBK	125	100	245	370	345	370	280	230	180	200	80	90	380	360	310	270	25	19	80	91	38	8	5	10	240
150X100CBJ	150	100	202.5	327.5	340	310	280	200	175	185	60	70	300	290	250	230	20	19	80	88	38	8	5	10	170
150X100CBK	150	100	272	403	380	415	305	255	180	230	90	100	430	400	350	300	25	19	90	99	48	9	5.5	14	310
150X125CBH	150	125	210	335	360	330	290	180	185	175	80	90	380	360	310	270	25	19	80	84.5	38	8	5	10	170
150X125CBJ	150	125	234	366	370	340	315	224	205	205	80	90	380	360	310	270	25	19	90	102	48	9	5.5	14	200
150X150CBG	150	150	225	320	350	305	275	170	175	165	80	90	380	360	310	270	25	19	63	85	28	8	5	10	150
200X100CBK	200	100	285	420.5	430	465	350	275	185	255	100	110	480	450	390	340	25	24	100	109	48	9	5.5	14	430
200X125CBH	200	125	221.5	348.5	385	340	265	215	200	200	80	90	380	360	310	270	25	19	80	88	38	8	5	10	190
200X125CBJ	200	125	221.5	348.5	405	400	280	240	210	230	80	90	380	360	310	270	25	19	80	88	38	8	5	10	240
200X150CBG	200	150	255	350	370	330	285	205	185	185	80	100	430	400	350	300	25	19	80	91	28	8	5	10	210
200X150CBH	200	150	242.5	352.5	395	380	260	240	210	220	90	100	430	400	350	300	25	19	80	90	28	8	5	10	260
200X150CBJ	200	150	265.5	389.5	425	405	390	275	230	260	90	100	430	400	350	300	25	19	90	96	48	9	5.5	14	380
200X200CBF	200	200	245	340	385	380	320	210	200	200	90	100	430	400	350	300	25	19	63	70	28	8	5	10	230
250X150CBH	250	150	272	408	460	425	290	264	230	250	100	110	480	450	390	340	25	24	90	101	38	8	5	10	340
250X150CBJ	250	150	294	451	480	450	440	310	250	290	100	110	480	450	390	340	25	24	100	111	55	10	6	16	470
250X150CBK	250	150	345	520	480	520	390	310	205	285	110	120	550	520	450	400	30	24	110	123	65	11	7	18	630
250X200CBF	250	200	275	390	450	395	315	243	225	225	100	110	480	450	390	340	25	24	80	86	38	8	5	10	320
250X200CBGX	250	200	270	385	435	370	300	225	210	210	90	110	480	450	390	340	25	24	80	86	38	8	5	10	270
250X200CBGY	250	200	290	415	475	415	340	250	235	235	100	120	550	520	450	400	30	24	90	99	48	9	5.5	14	340
250X200CBH	250	200	284.5	420.5	505	475	350	280	260	280	110	120	550	520	450	400	30	24	100	109	48	9	5.5	14	470
300X150CBK	300	150	350	535	485	600	440	345	235	320	110	120	550	520	450	400	25	24	125	133	65	11	7	18	860
300X200CBG	300	200	310	460	525	465	355	270	260	265	110	120	550	520	450	400	30	24	100	115	48	9	5.5	14	580
300X200CBH	300	200	310	490	560	535	405	320	295	315	110	120	550	520	450	400	30	24	110	124	55	10	6	16	690
300X200CBJX	300	200	321	480	545	505	495	336	280	320	110	130	550	520	450	400	30	24	110	124.5	65	11	7	18	720
300X200CBJY	300	200	349	526	565	565	550	374	315	360	120	120	550	520	450	400	30	24	125	132.5	75	12	7.5	20	870
300X250CBFX	300	250	280	415	505	445	350	265	255	255	100	120	550	520	450	400	30	24	90	101	38	8	5	10	480
300X250CBFY	300	250	335	460	520	495	355	300	275	285	110	120	550	520	450	400	30	26	90	105	48	9	5.5	14	590
300X250CBG	300	250	370	525	600	560	450	305	307	300	135	150	620	700	500	550	38	26	110	121	65	11	7	18	780
300X250CBH	300	250	350	535	625	600	450	355	340	355	135	150	620	700	500	550	38	26	125	133	65	11	7	18	860
350X250CBG	350	250	390	570	585	585	440	340	270	335	135	150	620	700	500	550	38	26	125	132	75	12	7.5	20	890
350X250CBH	350	250	365	555	665	675	500	395	270	395	120	140	800	800	720	660	30	28	125	137	75	12	7.5	20	1180
350X300CBF	350	300	360	510	600	560	450	330	275	320	130	150	620	700	500	550	38	26	100	107	55	10	6	16	830
400X300CBG	400	300	440	630	625	660	510	380	310	375	110	140	800	700	720	560	38	28	125	158	85	14	9	22	1400
400X350CBF	400	350	420	575	645	625	510	370	321	360	150	135	700	700	550	550	38	26	110	124.5	65	11	7	18	1050

DIMENSIONS - Dimensions of Bare Shaft Pump

C-3


■ 6P

Units:mm

MODEL	Size		Pump																Shaft						Wt (KG)
	Ds	Dd	A	B	C	E	F	G	H	I	J	K	M	N	O	P	Q	Z	L	R	T	U	V	W	
350X250CBH	350	250	365	555	665	675	500	395	270	395	120	140	800	800	720	660	30	28	125	137	75	12	7.5	20	1180
350X250CBJ	350	250	394.5	620.5	645	635	615	420	335	405	120	140	700	700	620	560	30	28	140	160	95	14	9	25	1240
400X300CBG	400	300	440	630	625	660	510	380	310	375	110	140	800	700	720	560	38	28	125	158	85	14	9	22	1400
400X300CBH	400	300	450	685	715	755	515	445	320	445	110	140	800	800	720	660	30	28	160	179	95	14	9	25	1670
400X300CBJX	400	300	559	756	725	710	690	470	380	455	140	140	800	800	660	660	30	28	160	170	105	16	10	28	1940
400X300CBJY	400	300	432	658	815	800	630	515	420	510	130	160	860	900	780	740	35	30	140	145	95	14	9	25	1260
400X400CBF	400	400	470	645	725	690	505	410	380	405	130	160	860	800	780	640	35	30	125	132	75	12	7.5	20	1550
450X300CBH	450	300	475.5	679.5	800	800	580	490	380	500	130	160	860	860	780	740	35	30	140	144.5	85	14	9	22	1400
450X350CBG	450	350	414	606	705	740	555	420	360	420	120	160	860	800	780	640	35	30	125	148	75	12	7.5	20	1110
450X400CBF	450	400	454	620	780	750	565	450	415	445	130	160	920	900	840	740	30	30	125	134	65	11	7	18	1340
500X350CBG	500	350	475.5	679.5	775	830	600	465	395	470	120	160	920	900	840	740	35	30	140	162	85	14	9	22	1460

DIMENSIONS - Dimension of Pump with Motor

C-4



■ Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	24	2	8	φ23
100	160	185	225	26	2	8	φ23
125	195	225	270	26	2	8	φ25
150	230	260	305	28	2	12	φ25
* 200	275	305	350	30	2	12	φ25
* 250	345	380	430	34	2	12	φ27
* 300	395	430	480	36	3	16	φ27
* 350	440	480	540	38	3	16	φ33
* 400	495	540	605	42	3	16	φ33
* 450	560	605	675	46	3	20	φ33
* 500	615	660	730	50	3	20	φ33

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG
use the legal dimensions of Ductile Cast Iron

■ Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	132	160	200	22	3	8	φ19
100	156	180	220	24	3	8	φ19
125	184	210	250	26	3	8	φ19
150	211	240	285	26	3	8	φ23
* 200	266	295	340	30	3	12	φ23
* 250	319	355	405	32	3	12	φ28
* 300	370	410	460	32	4	12	φ28
* 350	429	470	520	36	4	16	φ28
* 400	480	525	580	38	4	16	φ31
* 450	548	585	640	40	4	20	φ31
* 500	609	650	715	42	4	20	φ34

* 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG
use the legal dimensions of Ductile Cast Iron

*■ Ductile Cast Iron 16bar Flange (JIS 16K)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	275	305	350	26	2	12	φ25
250	345	380	430	28	2	12	φ27
300	395	430	480	30	3	16	φ27
350	440	480	540	34	3	16	φ33
400	495	540	605	38	3	16	φ33
450	560	605	675	40	3	20	φ33
500	615	660	730	42	3	20	φ33

*■ Ductile Cast Iron 16bar Flange (GB PN16)

Units:mm

D	g	e	f	t	t1	n	h
80	-	-	-	-	-	-	-
100	-	-	-	-	-	-	-
125	-	-	-	-	-	-	-
150	-	-	-	-	-	-	-
200	266	295	340	20	3	12	φ23
250	319	355	405	22	3	12	φ28
300	370	410	460	24.5	4	12	φ28
350	429	470	520	26.5	4	16	φ28
400	480	525	580	28	4	16	φ31
450	548	585	640	30	4	20	φ31
500	609	650	715	31.5	4	20	φ34

DIMENSIONS - Dimension of Pump with Motor

C-5

4P																											units:mm																			
Model	Motor	Size		Pump								Motor					Common Base												Total																	
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)																
125X80CBJ	4.0	125	80	188	272	310	300	250	170	165	165	110	112M	200	195	188.5	45	170	410	125	510	-	760	330	290	4-φ15	56	3	858	211																
	132S												239	241	212	61	130			540	-	800	57				943		228																	
	132M												258	267		73	140			560	-	840	60				988		243																	
	160M												323	291	255	103	150			620	-	920	74				1077		287																	
125X80CBK	11	125	80	225	310	290	330	250	195	140	180	170	160M	323	291	255	103	190	410	160	660	-	980	370	330	4-φ19	76	4	1152	349																
	160L												345	329	130		170			690	-	1030	79				1212		379																	
	180M												351.5	331.5	165		180			700	-	1040	80				1221		415																	
	180L												370.5	347.5	180	175	720			-	1070	83	1256	433																						
	200L												395.5	376.5	200	185	750			-	1120	90	1311	498																						
	225S												432	388	227	190	760			-	1140	92	1359	560																						
125X100CBK	18.5	125	100	245	370	345	370	280	230	180	200	240	180M	351.5	331.5	270	165	210	465	185	750	-	1120	400	360	4-φ19	92	3	1301	497																
	180L												370.5	347.5	180		190			770	-	1150	94				1336		514																	
	200L												395.5	376.5	200		210			800	-	1200	119				1391		597																	
	225S												432	388	227	210	820			-	1220	123	1439	661																						
	225M												444.5	400.5	327	210	840			-	1250	126	1464	688																						
	250M												482.5	434.5	373	210	880			-	1310	139	1536	789																						
150X100CBJ	7.5	150	100	202.5	327.5	340	310	280	200	175	185	170	132M	258	267	212	73	170	460	150	600	-	900	330	290	4-φ19	71	3	1058	314																
	160M												323	291	255	103	160			660	-	980	78				1147		351																	
	160L												345	329	130	170	690			-	1030	82	1207				382																			
	180M												351.5	331.5	165	170	720			-	1070	83	1216	418																						
	180L												370.5	347.5	180	175	750			-	1120	86	1251	436																						
	200L												395.5	376.5	200	185	760			-	1140	92	1301	497																						
150X100CBK	30	150	100	272	403	380	415	305	255	180	230	310	200L	395.5	376.5	300	238	235	520	210	840	-	1260	440	390	4-φ24	131	4	1451	679																
	225S												432	388	327	238	215			860	-	1280	135				1499		743																	
	225M												444.5	400.5	327	238	215			880	-	1310	138				1524		770																	
	250M												482.5	434.5	373	238	225			920	-	1370	152	1596	872																					
	280S												514	462	413	555	235			950	-	1420	174	1655	1039																					
	280M												539.5	487.5	413	610	245			980	-	1470	180	1706	1100																					
150X125CBH	5.5	150	125	210	335	360	330	290	180	185	175	170	132S	239	241	212	61	210	480	150	600	-	900	400	360	4-φ19	80	3	1028	311																
	132M												258	267	73	155	630			-	940	83	1073				326																			
	160M												323	291	255	103	170			690	-	1030	89				1162		362																	
	160L												345	329	255	103	185			740	-	1110	95				1277		425																	
150X125CBJ	15	150	125	234	366	370	340	315	224	205	205	200	180M	351.5	331.5	270	165	210	490	185	740	-	1110	400	360	4-φ19	94	3	1286	459																
	180L												370.5	347.5	180		190			770	-	1150	97				1321		477																	
	200L												395.5	376.5	200		210			800	-	1190	123				1376		561																	
	225S												432	388	327	238	200			820	-	1220	128	1424	626																					
	150X150CBG												7.5	150	150	225	320			350	305	275	170	175	165		150		132M	258	267	212	73	210	470	155	620	-	930	400	360	4-φ19	82	3	1073	305
	11												160M																323	291	255	103	165			680	-	1010	87				1162		340	
15	160L	345	329	130	175	710	-	1060	91	1222	371																																			
200X100CBK	55	200	100	285	420.5	430	465	350	275	185	255	430	250M					482.5	434.5							373		410	260	570	235	940	-			1410	560	510	4-φ24				168		4	1626.5
75	280S												514	462	413	555	240	980	-	1460	194	1685.5	1179																							
90	280M												539.5	487.5	413	610	250	1020	-	1520	201	1736.5	1241																							
110	315S												589	554	750	260	1050	-	1570	272	1852.5	1452																								
132	315M													482	875		-			295		1600																								
160	315L												614.5	708.5	960		-			296	2032.5	1685																								
185				1070							1796																																			
200X125CBH	7.5	200	125	221.5	348.5	385	340	265	215	200	200	190	132M	258	267	212	73	210	505	160	640	-	960	400	360	4-φ19	86	3	1098	349																
	11												160M	323	291	255	103			170	700	-	1040				92		1187	385																
	15												160L	345	329	130	180			730	-	1090	96				1247		416																	
	18.5												180M	351.5	331.5	165	190			760	-	1130	99				1291		469																	
	22												180L	370.5	347.5	180																														
200X125CBJ	22	200	125	221.5	348.5	405	400	280	240	210	230	240	180L	370.5	347.5	270	180	210	525	185	760	-	1130	400	360	4-φ19	101	4	1291	521																
	30												200L	395.5	376.5	300	238			195	790	-	1180				110		1346	588																
	37												225S	432	388	327	298			200	800	-	1200				134		1394	672																
	45												225M	444.5	400.5	327	322			205	820	-	1230	137	1419		699																			
	55												250M	482.5	434.5	373	410			215	860	-	1290	151	1491		801																			
	75												280S	514	462	413	555			220	900	-	1340	173	1550		968																			
200X150CBG	11	200	150	255	350	370	330	285	205	185	185	210	160M	323	291	255	103	235	490	175	720	-	1070	440	400	4-φ19	97	3	1222	410																
	15												160L	345	329		130			185	740	-	1110				101		1282	441																
	18.5												180M	351.5	331.5		165			190	750	-	1120				100		1291	475																
	22												180L	370.5	347.5	180							104				1326		494																	
200X150CBH	15	200	150	242.5	352.5	395	380	260	240	210	220	260	160L	345	329	255	130	235	515	185	750	-	1120	440	400	4-φ19	104	3	1272	494																
	18.5												180M	351.5	331.5	165	190			780	-	1160	103				1281		528																	
	22												180L	370.5	347.5	180							107				1316		547																	
	30												200L	395.5	376.5	300	238			200	810	-	1210				132		1371	630																
	37												225S	432	388	327	298			205	820	-	1230				137		1419	695																

*1: The motor without size is high voltage motor, please contact us.

DIMENSIONS - Dimension of Pump with Motor

C-6

4P

units:mm

Model	Motor	Size		Pump								Motor					Common Base										Total									
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)						
200X150CBJ	37	200	150	265.5	389.5	425	405	390	275	230	260	380	225S	432	388	327	298	235	565	210	850	-	1270	500	450	4-φ24	143	4	1479	821						
	45												225M	444.5	400.5	327	322										215		860	-	1290	560	510	146	1504	848
	55												250M	482.5	434.5	373	410										225		910	-	1360	620	570	161	1576	951
	75												280S	514	462	413	555										235		940	-	1410	620	570	187	1635	1122
	90												280M	539.5	487.5	413	610										240		980	-	1460	620	570	194	1686	1184
	110												315S	589	554	482	750										605		1020	-	1520	700	640	264	1802	1394
200X200CBF	11	200	200	245	340	385	380	320	210	200	200	230	160M	323	291	255	103	235	505	175	710	-	1060	440	400	4-φ19	98	3	1202	431						
	15												160L	345	329	255	130										102		1262	462						
	30												200L	395.5	376.5	300	238										153		1456	731						
250X150CBH	37	250	150	272	408	460	425	290	264	230	250	340	225S	432	388	327	298	260	600	215	880	-	1310	500	450	4-φ24	155	4	1504	793						
	45												225M	444.5	400.5	327	322										159	1529	821							
	55												250M	482.5	434.5	373	410										174	1601	924							
	75												280S	514	462	413	555										203	1660	1098							
	90												315S	589	554	482	750										270	1776	1350							
250X150CBJ	75	250	150	294	451	480	450	440	310	250	290	470	280S	514	462	413	555	260	660	620	245	1000	-	1490	620	570	4-φ24	210	4	1725	1235					
	90												280M	539.5	487.5	413	610											270		1776	1350					
	110												315S	589	554	482	750											291		1892	1511					
	132												315M	589	554	482	875											316		1661	1661					
	160												315L	614.5	708.5	482	960											317		2072	1747					
	185												315L	614.5	708.5	482	1070											317		2072	1747					
250X150CBK	90	250	150	345	520	480	520	390	310	205	285	630	280M	539.5	487.5	413	610	295	660	275	1100	-	1650	620	560	4-φ26	281	4	1896	1521						
	110												315S	589	554	482	750										318		2012	1698						
	132												315M	589	554	482	875										326		1831	1918						
	160												315L	614.5	708.5	482	960										328		2192	2028						
	185												315L	614.5	708.5	482	1070										328		2192	2028						
	200												355M	704	816	646	1640										378		2390	2638						
	220												355M	704	816	646	1640										378		2390	2648						
	250												355M	704	816	646	1640										378		2390	2698						
	280												355L	704	816	646	1690										378		2390	2698						
	315												355L	704	816	646	1790										378		2390	2798						
	250X200CBF												18.5	250	200	275	390										450		395	315	243	225	225	320	180M	351.5
22		180L	370.5	347.5	270	180	144	1386	644																											
30		200L	395.5	376.5	300	238	151	1441	709																											
250X200CBGX	22	250	200	270	385	435	370	300	225	210	210	270	180L	370.5	347.5	270	180	260	575	200	820	-	1220	490	440	4-φ24	141	3	1376	591						
	30												200L	395.5	376.5	300	238										148		1431	656						
	37												225S	432	388	327	298										150		1479	718						
250X200CBGY	37	250	200	290	415	475	415	340	250	235	235	340	225S	432	388	327	298	295	615	225	900	-	1350	560	510	4-φ24	169	4	1529	807						
	45												225M	444.5	400.5	327	322										173		1554	835						
	55												250M	482.5	434.5	373	410										184		1626	934						
	75												280S	514	462	413	555										214		1685	1109						
	90												315S	589	554	482	750										270		1776	1350						
250X200CBH	45	250	200	284.5	420.5	505	475	350	280	260	280	470	225M	444.5	400.5	327	322	295	645	230	920	-	1380	560	510	4-φ24	178	4	1554	970						
	55												250M	482.5	434.5	373	410										191		1626	1071						
	75												280S	514	462	413	555										224		1685	1249						
	90												280M	539.5	487.5	413	610										284		1736	1364						
	110												315S	589	554	482	750										306		1852	1526						
	132												315M	614.5	708.5	482	875										331		2032	1676						
300X150CBK	160	300	150	350	535	485	600	440	345	235	320	860	315L	614.5	708.5	482	960	295	665	305	1220	-	1830	700	640	4-φ26	330	4	2212	2150						
	185																1070												2270	2871						
	200																1080												2881	2931						
	220												355M	704	816	646	1640			381	5	2410	2881	3031												
	250																1690			381	5	2410	2931	3031												
	280																1790			381	5	2410	2991	3031												
	315												315L	614.5	708.5	482	1070			381	5	2410	2991	3031												
	355												315L	614.5	708.5	482	1070			381	5	2410	2991	3031												
	400												315L	614.5	708.5	482	1070			381	5	2410	2991	3031												
	450												315L	614.5	708.5	482	1070			381	5	2410	2991	3031												
	500												315L	614.5	708.5	482	1070			381	5	2410	2991	3031												
630	315L	614.5	708.5	482	1070	381	5	2410	2991	3031																										
300X200CBG	55	300	200	310	460	525	465	355	270	260	265	580	250M	482.5	434.5	373	410	295	645	260	980	490	1500	560	530	6-φ19	171	4	1691	1161						
	75												280S	514	462	413	555										199		1750	1334						
	90												280M	539.5	487.5	413	610										292		1801	1482						
	110												315S	589	554	482	750										314		1917	1644						
	132												315M	614.5	708.5	482	875										341		2097	1796						
300X200CBH	90	300	200	310	490	560	535	405	320	295	315	690	280M	539.5	487.5	413	610	295	740	270	1080	-	1620	620	560	4-φ26	304	4	1831	1604						
	110												315S	589	554	482	750										328		1947	1768						
	132												315M	589	554	482	875										356		2127	1921						
	160												315L	614.5	708.5	482	960										357		2127	2007						
	185												315L	614.5	708.5	482	1070										357		2127	2117						
	200												315L	614.5	708.5	482	1080										357		2127	2127						

DIMENSIONS - Dimension of Pump with Motor

C-7

4P

units:mm

Model	Motor	Size		Pump								Motor					Common Base										Total					
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)		
300X200CBJX	132	300	200	321	480	545	505	495	336	280	320	720	315M	614.5	708.5	482	875	295	725		295	1190	-	1780	700	640	4-φ26	351	4	2128	1946	
	160												960				-						2033									
	185												1070				-						2143									
	200												1080				-						2153									
	220												704	816	646	1630	320	1300	-	1940	830	770	389	5	2326	2739						
	250															1640			-							2749						
	280															1690			-							2799						
	315															1790			-							2899						
	355												*1																			
300X200CBJY	200	300	200	349	526	565	565	550	374	315	360	870	315L	614.5	708.5	482	1080	295	745	330	1320	-	1820	700	640	4-φ26	360	4	2202	2310		
	220												1630				-					2916										
	250												1640				-					2926										
	280												1690				-					2976										
	315												1790	-	3076																	
	355												*1																			
	400												*1																			
	450												*1																			
	500												*1																			
630	*1																															
300X250CBFX	30	300	250	280	415	505	445	350	265	255	255	480	200L	395.5	376.5	300	238	295	645	220	890	-	1330	560	510	4-φ24	173	4	1471	891		
	37												225S	432	388	327	298			225	900	-	1350				175		1519	953		
	45												225M	444.5	400.5	322	322			230	920	-	1380				178		1544	980		
	55												250M	482.5	434.5	373	410			240	960	-	1440				191		1616	1081		
300X250CBFY	55	300	250	335	460	520	495	355	300	275	285	590	250M	482.5	434.5	373	410	295	665	245	1000	-	1490	560	510	4-φ24	204	4	1716	1204		
	75												280S	514	462	413	555			255	1030	-	1540				238		1775	1383		
	90												280M	539.5	487.5	610	610			705	265	1060	-	1590			299		1826	1499		
													315S	589	554	750	750			300	1145	-	1745	323			2042		1853			
300X250CBG	110	300	250	370	525	600	560	450	305	307	300	780	315M	614.5	708.5	482	875	330	745	310	1230	-	1850	740	700	4-φ24	350	4	2222	2005		
	132												-				2161															
	160												-				2271															
	185												-				2281															
	200												-																			
	220												355M	704	816	646	1630	200			1620	810	2020	830			770	6-φ26	480	5	2420	2890
300X250CBH	160	300	250	350	535	625	600	450	355	340	355	860	315L	614.5	708.5	482	960	330	810	310	1250	-	1870	740	680	4-φ26	431	4	2212	2251		
	185												-				2361															
	200												-				2371															
	220												-				2982															
	250												195				1640				820	2030	830	770	6-φ26	492	5	2410	2992			
	280												355L	704	816	646	1690	-			3042											
315	*1																															
355	*1																															
350X250CBG	185	350	250	390	570	585	585	440	340	270	335	890	315L	614.5	708.5	482	1070	330	730	330	1260	-	1920	740	700	4-φ24	349	4	2287	2309		
	200												1080				-				2319											
	220												1630				-				2995											
	250												1640				-				3005											
	280												704	816	646	1690	770	350	1390	695	2090	810	740	6-φ26	475	5	2485	3055				
	315															1790									-		3155					
	355															*1																
400	*1																															
350X250CBH	250	350	250	365	555	665	675	500	395	270	395	1180	355M	704	816	646	1640	420	890	210	1720	860	2140	840	770	6-φ28	628	5	2445	3448		
	280												1690				-										3498					
	315												1790				-										3598					
	355												*1																			
	400												*1																			
350X300CBF	90	350	300	360	510	600	560	450	330	275	320	830	280M	539.5	487.5	413	610	330	745	290	1115	-	1695	740	700	4-φ24	310	4	1901	1750		
	110												315S	589	554	750	285			1160	-	1730	390				2017		1970			
	132												315M	614.5	708.5	482	875			305	1230	-	1840	680			4-φ26		419	2197	2124	
	160												960				-												2209			
400X300CBG	315	400	300	440	630	625	660	510	380	310	375	1400	355L	704	816	646	1790	425	810	390	1555	777.5	2335	810	740	6-φ26		530	5		2595	3720
	355												*1																			
	400												*1																			
	450												*1																			
	500												*1																			
	630												*1																			
800	*1																															
400X350CBF	160	400	350	420	575	645	625	510	370	321	360	1050	315L	614.5	708.5	482	960	375	790	330	1285	-	1945	750	710	4-φ24	374	4	2322	2384		
	185												1070				-					2494										
	200												1080				-					2504										
	220												1630				-					3305										
	250												1640	-	3315																	

DIMENSIONS - Dimension of Pump with Motor

C-9

■6P


units:mm

Model	Motor	Size		Pump									Motor					Common Base										Total			
	kW	Ds	Dd	A	B	C	E	F	G	H	I	Wt (KG)	Frame	MR	MA	Hm	Wt (KG)	BJ	BC	BN	BM	BM1	BL	BW	BY	n-fd	Wt (KG)	T	L	Wt (KG)	
450X300CBH	185	450	300	475.5	679.5	800	800	580	490	380	500	1400	355M	704	816	646	1760	450	1030	225	1840	920	2290	900	830	6-φ28	787	5	2680	3947	
450X300CBH	200												1870				4057														
450X300CBH	220												1950				4131														
450X300CBH	250																														
450X300CBH	280																														
450X300CBH	315																														
450X300CBH	355																														
450X300CBH	400																														
450X300CBH	450																														
450X300CBH	500																														
450X300CBH	630																														
450X350CBG	110	450	350	414	606	705	740	555	420	360	420	1110	315L	614.5	708.5	482	975	450	895	200	1660	830	2060	840	780	6-φ26	534	4	2347	2619	
450X350CBG	132												1030				2674														
450X350CBG	160												1630				3428														
450X350CBG	185												704	816	646	1760	935	220	1780	890	2220	840	770	6-φ28	688	5	2545	3558			
450X350CBG	220																											1870	3668		
450X350CBG	250																											1950	3748		
450X350CBG	280																														
450X350CBG	315																														
450X350CBG	355																														
450X400CBF	90												450	400	454	620	780	750	565	450	415	445	1340	315M	614.5	708.5	482	835	480	1010	210
450X400CBF	110	975	3037																												
450X400CBF	132	1030	3092																												
450X400CBF	160	704	816	646	1630	220	1820	910	2260	940	870	6-φ28												762	5	2599	3732				
450X400CBF	185																										1760	3862			
450X400CBF	200																										1870	3972			
450X400CBF	220	704	816	646	1760	230	1860	930	2320	940	870	6-φ28												790	5	2680	4010				
450X400CBF	250																										1870	4120			
																											1950	4200			
500X350CBG	200	500	350	475.5	679.5	775	830	600	465	395	470	1460												355M	704	816	646	1760	480	1005	230
500X350CBG	220												1870	4120																	
500X350CBG	250												1950	4200																	
500X350CBG	280																														
500X350CBG	315																														
500X350CBG	355																														
500X350CBG	400																														
500X350CBG	450																														
500X350CBG	500																														
500X350CBG	630																														
500X350CBG	800																														

*1: The motor without size is high voltage motor, please contact us.

CONSTRUCTION - Sectional View of Pump

D-1

**Mechanical Seal Type**

No	Part Name	GB Material	JIS Material	Qty
053-2	Bearing Cover	HT250	FC250	1
053-1	Bearing Cover	HT250	FC250	1
051-2	Bearing Unit	HT200	FC200	1
051-1	Bearing Unit	HT200	FC200	1
045	O-ring	NBR	NBR	2
041	Impeller Nut	ZCuSn5Pb5Zn5	CAC406	1
039-2	Coupling Key	50	S50C	1
039-1	Impeller Key	20Cr13	SUS420J1	1
031	Shaft	20Cr13	SUS420J1	1
021	Impeller	ZCuSn5Pb5Zn5 (or ZG0Cr18Ni9) ^{*2}	CAC406 (or SCS13) ^{*2}	1
011-2	Side Cover	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
011-1	Side Cover	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
006	Casing Lower Half	HT250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1
004	Casing Upper Half	T250 (or QT450-10) ^{*1}	FC250 (or FCD450) ^{*1}	1

No	Part Name	GB Material	JIS Material	Qty
162-3	Plug1"	Q235-A	SS	1
162-2	Plug1/2"	Q235-A	SS	1
162-1	Plug3/8"	Q235-A	SS	2
156	Lock Pin	06Cr19Ni10	SUS304	2
136	Bearing Washer	Q235-A	SS	1
129	Bearing Nut	Q235-A	SS	1
117-1	Gasket (Casing)	-	Fiber Materials	1
111-2	Mechanical Seal	-	-	1
111-1	Mechanical Seal	-	-	1
107-2	Casing Wear Ring	ZCuSn5Pb5Zn5	CAC406	1
107-1	Casing Wear Ring	ZCuSn5Pb5Zn5	CAC406	1
093-2	Deflector (CCP Side)	NBR	NBR	1
093-1	Deflector (CP Side)	NBR	NBR	1


*1: The material is changed to ductile cast iron for model 300X200CBJY, 350X250CBJ, 400X300CBH, 400X300CBJX, 400X300CBJY, 400X400CBF, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG.

*2: The material is changed to cast stainless steel for model 400X300CBJX, 400X300CBJY, 450X300CBH, 450X350CBG, 450X400CBF, 500X350CBG.

CONSTRUCTION - Sectional View of Mechanical Seal


D-2

Standard shaft seal (16 bar) : Type 2100 / Diameter of axle < 100mm




Part No.	Part Name	Material	Qty/unit
1	Bellows	NBR	1
2	Primary Ring	Carbon	1
3	Drive Band	316 Stainless Steel	1
4	Spring	316 Stainless Steel	1
5	O-ring	NBR	1
6	Mating Ring	Ceramic	1

Standard shaft seal (16 bar) : Type 8-1 / Diameter of axle > 100mm



Part No.	Part Name	Material	Qty/unit
1	Retainer	316 Stainless Steel	1
2	Holding screw	316 Stainless Steel	1
3	Spring	316 Stainless Steel	1
4	O-ring	FPM	1
5	Primary Ring	Carbon	1
6	Mating Ring	Silicon carbide	1
7	O-ring	FPM	1
8	Pin	304 Stainless Steel	1

60Hz - 4P




Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity $1.0\text{mPa} \cdot \text{s}$.

Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

60HZ - 4P




Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity 1.0mPa • s.

Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

60Hz - 6P




Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity 1.0mPa · s.

Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

60Hz - 6P



Note1 : The value inside the broken lines are motor output(kW) in case of density 1.0kg/L and viscosity 1.0mPa • s.


Note2 : The indicated motor output(kW) value includes the following safety margins ;

Up to 7.5kW : 15%

11kW and above : 10%

Performance Curve

4 Poles



S8-1831137-01


Performance Curve

4 Poles

125X80CBK

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1765 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831147-00


Performance Curve

4 Poles

125X100CBK

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1765 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831148-00

Performance Curve

4 Poles



S8-1831138-01


Performance Curve

4 Poles

150X100CBK

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1780 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831149-00

Performance Curve

4 Poles




S8-1831128-00

Performance Curve

4 Poles


150X125CBJ	According to ISO testing code 9906 Grade 2B Class 2
60 Hz (Speed 1765 min ⁻¹)	DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831139-01

Performance Curve


4 Poles



S8-1831120-00

Performance Curve


4 Poles



S8-1831150-00

Performance Curve


4 Poles



S8-1831129-00

Performance Curve


4 Poles



S8-1831140-01

Performance Curve

4 Poles



S8-1831121-00


Performance Curve

4 Poles

200X150CBH

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1765 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831130-00


Performance Curve

4 Poles

200X150CBJ

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1780 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831141-01


Performance Curve

4 Poles

200X200CBF

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1765 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831113-00

Performance Curve


4 Poles



S8-1831131-00

Performance Curve


4 Poles



S8-1831142-01

Performance Curve

4 Poles



S8-1831114-00


Performance Curve

4 Poles

250X150CBK

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1790 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831151-00


Performance Curve

4 Poles

250X200CBGX

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1765 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831122-00

Performance Curve


4 Poles



S8-1831123-00

Performance Curve


4 Poles



S8-1831132-00

Performance Curve


4 Poles



S8-1831152-00

Performance Curve

4 Poles




S8-1831124-00

Performance Curve

4 Poles


300X200CBH	According to ISO testing code 9906 Grade 2B Class 2
60 Hz (Speed 1790 min ⁻¹)	DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831133-01

Performance Curve


4 Poles



S8-1831143-01

Performance Curve

4 Poles



S8-1831144-01


Performance Curve

4 Poles

300X250CBFX

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1780 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831115-00

Performance Curve


4 Poles



S8-1831116-00

Performance Curve


4 Poles



S8-1831125-00

Performance Curve


4 Poles



S8-1831134-00

Performance Curve


4 Poles



S8-1831126-00

Performance Curve

4 Poles



S8-1831135-00


Performance Curve

4 Poles

350X300CBF

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1790 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



S8-1831117-00

Performance Curve


4 Poles



S8-1831127-00

Performance Curve


4 Poles



S8-1831118-00

Performance Curve

6 Poles




F8-1932898-00

Performance Curve

6 Poles


350X250CBJ	According to ISO testing code 9906 Grade 2B Class 2
60 Hz (Speed 1190 min ⁻¹)	DENSITY= 1.0 kg/l, VISCOSITY= 1.0 mPa.s



F8-1932899-00

Performance Curve

6 Poles



F8-1932900-00


Performance Curve

6 Poles

400X300CBH

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1190 min⁻¹)

DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932901-00


Performance Curve

6 Poles

400X300CBJX

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1190 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932902-00

Performance Curve


6 Poles



F8-1932903-00

Performance Curve


6 Poles



F8-1932904-00

Performance Curve


6 Poles



F8-1932905-00

Performance Curve

6 Poles



F8-1932906-00


Performance Curve

6 Poles

450X400CBF

According to ISO testing
code 9906 Grade 2B Class 260 Hz (Speed 1190 min⁻¹)


DENSITY=1.0 kg/l, VISCOSITY=1.0 mPa·s



F8-1932908-00

Performance Curve

6 Poles



F8-1932909-00